

FEATURES

- 11,000 RPM
- 1 HP Motor eliminates stall and increases reliability
- Spindle lock for easy wheel change
- Speed control switch located at the top of the grip for added control
- Multi positional rotational guard improves access
- The composite grip and throttle trigger have been ergonomically designed to provide unmatched comfort for the user
- 360 ° Rotational exhaust

SPECIFICATIONS

Length (in.)	8.75
Width (in.)	5.2
Height (in.)	2.8
Weight (lbs.)	2.25
Gears	Spiral Bevel
Exhaust	Rear
Air Cons. (CFM)	6
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4 NPT
Vibration Level (m/sec ²)	1.2
Noise Level d(B)A	88
Free Speed (RPM)	11000



Styled for perfection
and built to last!

Collet Size/Wheel Size (in.)	5/8 - 11
Motor (HP)	1

FEATURES

- 15,000 RPM
- .5 HP Motor
- Quiet tuned exhaust (80 dBA)
- Superior steel grade internal bearings for longer life
- Variable speed trigger with safety lock-off for better speed control
- Ergonomically designed composite overmold housing
- Tool will also accommodate 2" rol-loc sanding pad (Included)

SPECIFICATIONS

Length (in.)	7
Width (in.)	2.5
Height (in.)	2.55
Weight (lbs.)	1.5
Free Speed (BPM)	15000
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4 NPT
Vibration Level (m/sec ²)	0.6
Noise Level d(B)A	80



Styled for perfection
and built to last!



6265

6mm Angled 1.0 Hp Composite
Die Grinder

FEATURE

- Full 1.0 hp non-stall motor.
- Patented quiet tuned exhaust (82 dba).
- Superior steel grade internal bearings for longer life.
- Feather trigger for better speed control.
- Ergonomically designed housing.
- Most comfortable trigger in the industry.

SPECIFICATIONS

Free speed (rpm): 18,000	Weight (kg): 0.95
Motor (hp): 1.0	Length (mm): 241.30
Collet Size (mm): 6	Vibration level M/ Sec2: 2.9
Gears: Bevel Gears	Air Consistency (CFM): 4.2
Exhaust: Rear	Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6280

6mm Angled 0.75 HP Spindle Lock
Composite Die Grinder

FEATURE

- 18,000 rpm.
- .75 hp non stall motor.
- Spindle lock feature for easy accessory change.
- Speed control switch located at the top of the grip for added control.
- Erickson® style precision collet.
- Composite handle and grip for comfort.
- Low noise only 79 dba.

SPECIFICATIONS

Free speed (rpm): 18,000
Motor (hp): 0.75
Collet Size (mm): 6
Gears: Direct Drive
Exhaust: Rear

Weight (kg): 0.82
Length (mm): 117.8
Vibration level M/ Sec2: 2.5
Air Consistency (CFM): 4
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6295

115° Angle Die Grinder

FEATURE

- .6 hp motor.
- 18,000 rpm.
- Spindle lock feature for easy accessory change.
- Ergonomic composite over mold grip provides comfort.
- Speed control switch located at the top of the tool for added control.
- Rear exhaust.

SPECIFICATIONS

Free speed (rpm): 18,000

Motor (hp): 0.6

Wheel Size (in): 5

Gears: Bevel Gears

Cutting Capacity: 3/4" Rolled Steel / 18 Gauge

Exhaust: Rear

Weight (kg): 0.75

Length (mm): 198.00

Vibration level M/ Sec2: 12.7

Air Consistency (CFM): 6

Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6200

Composite Straight
Mini Die Grinder

FEATURE

- Patented quiet tuned exhaust (82 dba).
- Superior steel grade internal bearings for longer life.
- Feather trigger for better speed control.
- Ergonomically designed housing.
- Most comfortable trigger in the industry.

SPECIFICATIONS

Free speed (rpm): 20,000
Motor (hp): 0.40
Collet Size (mm): 6
Gears: Direct Drive
Exhaust: Rear

Weight (kg): 0.40
Length (mm): 165,10
Vibration level M/ Sec2: 2.9
Air Consistency (CFM): 4
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6255

Composite Angle
Die Grinder

FEATURE

- Patented quiet tuned exhaust (82 dba).
- Superior steel grade internal bearings for longer life.
- Feather trigger for better speed control.
- Ergonomically designed housing.
- Extended head to reach in tight spots.
- Most comfortable trigger in the industry.

SPECIFICATIONS

Free speed (rpm): 20,000
Motor (hp): 0.50
Collet Size (mm): 6
Gears: Spiral-Bevel
Exhaust: Rear

Weight (kg): 0.49
Length (mm): 177.80
Vibration level M/ Sec2: 2.5
Air Consistency (CFM): 6
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6270

6mm Extended Straight 1 Hp
Composite Die Grinder

FEATURE

- 20,000 rpm.
- 1.0 hp non stall motor.
- Patented "silencing technology" reduces noise to 85 dba.
- 6" extension to reach tight areas.
- Ergonomically designed housing.
- Most comfortable trigger in the industry.

SPECIFICATIONS

Free speed (rpm): 20,000
Motor (hp): 1.0
Collet Size (mm): 6
Gears: Direct Drive
Exhaust: Rear

Weight (kg): 1.18
Length (mm): 359,41
Vibration level M/ Sec2: 2.5
Air Consistency (CFM): 4.2
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6285

6mm Straight 1.0 HP Spindle Lock
Composite Die Grinder

FEATURE

- 20,000 rpm.
- .75 hp non stall motor.
- Spindle lock feature for easy accessory change.
- Speed control switch located on top of the grip for added control.
- Erickson® style precision collet.
- Composite handle and grip for comfort.
- Low noise only 79 dba.
- Low vibration only 2.5 m/sec2.

SPECIFICATIONS

Free speed (rpm): 20,000

Motor (hp): 0.75

Collet Size (mm): 6

Gears: Direct Drive

Exhaust: Rear

Weight (kg): 0.64

Length (mm): 117.8

Vibration level M/ Sec2: 2.5

Air Consistency (CFM): 4

Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURES

- 20,000 RPM
- .75 HP Non stall motor
- Speed control switch located under the trigger for added control
- Forward/Reverse switch located on top of the grip for easy directional changes
- Erickson® style precision collet
- Over-mold composite handle and grip for comfort
- Low noise only (79 dBA)
- Low vibration only 2.5 m/sec

SPECIFICATIONS

Length (in.)	7
Width (in.)	1.7
Height (in.)	1.7
Weight (lbs.)	1.4
Gears	Direct Drive
Exhaust	Rear
Air Cons. (CFM)	4
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4 NPT
Vibration Level (m/sec ²)	2.5
Noise Level d(B)A	79



Styled for perfection
and built to last!

Free Speed (RPM)	20000
Collet Size/Wheel Size (in.)	1/4
Motor (HP)	0.75

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
1660 Silver Beach Road-Suite 100 Lake Park, FL 33409

www.AIRCAT.com

(800) 356-3392



6201

Composite Straight
Die Grinder

FEATURE

- Patented quiet tuned exhaust (82 dba).
- Superior steel grade internal bearings for longer life.
- Feather trigger for better speed control.
- Ergonomically designed housing.
- Most comfortable trigger in the industry.

SPECIFICATIONS

Free speed (rpm): 22,000

Motor (hp): 0.50

Collet Size (mm): 6

Gears: Direct Drive

Exhaust: Rear

Weight (kg): 0.49

Length (mm): 215,00

Vibration level M/ Sec2: 3.1

Air Consistency (CFM): 6

Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6210

Composite Straight Die Grinder
Extended Shank

FEATURE

- Patented quiet tuned exhaust (82 dba).
- Superior steel grade internal bearings for longer life.
- Feather trigger for better speed control.
- Ergonomically designed housing.
- Extended head to reach in tight spots.
- Most comfortable trigger in the industry.

SPECIFICATIONS

Free speed (rpm): 20,000
Motor (hp): 0.50
Collet Size (mm): 6
Gears: Direct Drive
Exhaust: Rear

Weight (kg): 1.13
Length (mm): 342.90
Vibration level M/ Sec2: 3.1
Air Consistency (CFM): 6
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6260

Composite 1.0 Hp Straight
Die Grinder

FEATURE

- Full 1.0 hp non-stall motor.
- Patented quiet tuned exhaust (82 dba).
- Superior steel grade internal bearings for longer life.
- Feather trigger for better speed control.
- Ergonomically designed housing.
- Most comfortable trigger in the industry.

SPECIFICATIONS

Free speed (rpm): 22,000

Motor (hp): 1.0

Collet Size (mm): 6

Gears: Direct Drive

Exhaust: Rear

Weight (kg): 0.54

Length (mm): 234.95

Vibration level M/ Sec2: 2.3

Air Consistency (CFM): 6

Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM