



5300-A-T

Super Duty 0.498" Shank
Air Hammer

FEATURE

- 0.498" shank opening.
- 1760 blows / minute.
- Heavy duty "quick change chisel retainer" prevents chisels by-passing conventional spring retainers.
- Patented aircat ergonomically designed grip provides unmatched comfort for the user.
- Designed for ultra heavy duty and for driving out shackle and kingpins and cutting large bolts, nuts and fasteners.

SPECIFICATIONS

Free speed (rpm): 1,760
Pistol Stroke: 2-11/16
Shank Opening: .498"
Retainer: Quick Change
Valve: Plate

Weight (kg): 2.08
Length (mm): 227.07
Vibration level M/ Sec2: 17.4
Air Consistency (CFM): 6
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



5300-A

Super Duty 0.498" Shank
Air Hammer kit

FEATURE

- 0.498" shank opening.
- 1760 blows / minute.
- Heavy duty "quick change chisel retainer" prevents chisels by-passing conventional spring retainers.
- Patented aircat ergonomically designed grip provides unmatched comfort for the user.
- Designed for ultra heavy duty and for driving out shackle and kingpins and cutting large bolts, nuts and fasteners.
- Model ac5300-a includes: 4 pc. Chisel set / 902 | 907 | 909 | 910.

SPECIFICATIONS

Free speed (rpm): 1,760
Pistol Stroke: 2-11/16
Shank Opening: .498"
Retainer: Quick Change
Valve: Plate

Weight (kg): 2.08
Length (mm): 227.07
Vibration level M/ Sec2: 17.4
Air Consistency (CFM): 6
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



5200-A-T

COMPOSITE LONG STROKE AIR HAMMER

FEATURES

- 2,100 Blows per minute for fast cutting action
- High performance and low weight
- Multi-patented muffler/exhaust system gives this tool an extremely low noise of 88 dBA and vibration level of 4.2 m/sec²
- High quality safety-lock retainer for ease of chisel change and added safety
- Includes: Blow Mold Kit, 5 Pc. Chisel Set and Quick Change Retainer

SPECIFICATIONS

Free Speed (RPM)	2,100
Pistol Stroke (in.)	3-3/4
Shank Opening (in.)	.401
Retainer	Safety Lock
Valve	Plate
Weight (lbs.)	4.4
Length (in.)	11
Air Cons. (CFM)	6
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4



Styled for perfection and built to last!

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
851 Jupiter Park Lane / Jupiter, Florida 33458

www.AIRCAT.com

(800) 356-3392

FEATURES

- 2,500 BPM
- 3" Piston stroke
- Includes Quick change chisel retainer
- Variable speed trigger
- 4 position built-in air regulator

SPECIFICATIONS

Length (in.)	9.25
Width (in.)	5.38
Height (in.)	7.8
Weight (lbs.)	5.38
Free Speed (BPM)	2500
Retainer	Quick Change
Valve	Plate
Air Cons. (CFM)	4.2
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4 NPT
Vibration Level (m/sec ²)	19.5
Noise Level d(B)A	98.6
Piston Stroke (in.)	3



Styled for perfection
and built to last!

Shank Opening (in.)	0.401
---------------------	-------

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
1660 Silver Beach Road-Suite 100 Lake Park, FL 33409

www.AIRCAT.com

(800) 356-3392



5100-A-T

.401 Shank Composite Medium Stroke
Air Hammer

FEATURE

- 3,000 blows per minute for fast cutting action.
- High performance and low weight.
- Multi-patented muffler/exhaust system gives this tool and extremely low noise of 88 dba and vibration level of 4.2 m/sec².
- High quality safety-lock retainer for ease of chisel change and added safety.

SPECIFICATIONS

Free speed (rpm): 3,000
Pistol Stroke: 2-5/8
Shank Opening: .401"
Retainer: Safety-lock
Valve: Plate

Weight (kg): 1.49
Length (mm): 193.04
Vibration level M/ Sec²: 4.2
Air Consistency (CFM): 6
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



5100-A

0.401 Shank Composite
Hammer Kit

FEATURE

- 3,000 blows per minute for fast cutting action.
- High performance and low weight.
- Multi-patented muffler/exhaust system gives this tool and extremely low noise of 88 dba and vibration level of 4.2 m/sec².
- High quality safety-lock retainer for ease of chisel change and added safety.
- Model 5100-a includes: blow mold kit, 5 pc. Chisel set and quick change retainer.

SPECIFICATIONS

Free speed (rpm): 3,000
Pistol Stroke: 2-5/8
Shank Opening: .401"
Retainer: Safety-lock
Valve: Plate

Weight (kg): 1.49
Length (mm): 193.04
Vibration level M/ Sec²: 4.2
Air Consistency (CFM): 6
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM