



1057-TH

Stubby Impact Wrench

FEATURE

- Provides 680 nm maximum torque.
- Only 97.79 mm overall length.
- Low weight aluminum alloy housing.
- Reliable jumbo hammer mechanism delivers maximum power, while increasing reliability.
- Patented "silencing technology" reduces the noise level to 89 dba.
- Trigger mounted combined reverse and power management switch provides ultimate control and one-hand operation.

SPECIFICATIONS

Maximum torque (Nm): 680
Square drive (in.): 1/2
Impact per minute: 1600
Free speed (rpm): 9,000
Bolt capacity (mm): 13

Weight (kg): 1.27
Length (mm): 97.79
Vibration level M/ Sec2: 12.5
Air Consistency (CFM): 6.0
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1077-TH

3/8" COMPACT IMPACT WRENCH

FEATURES

- *Very compact, only 3.85" wide!*
- *Low weight aluminum alloy housing*
- *Reliable Jumbo hammer mechanism delivers maximum power, while increasing reliability*
- *Patented "Silencing Technology" reduces the noise level to 89 dBA*
- *Trigger mounted combined reverse and power management switch provides ultimate control and one-hand operation*

SPECIFICATIONS

Square Drive (in.)	3/8
Air Cons. (CFM)	6
Bolt Capacity (in.)	1/2
Air Inlet (in.) NPT/BSP	1/4
Rec. Hose Size (in.)	3/8
Weight (lbs.)	2.80
Length (in.)	3.85
Free Speed (RPM)	9,000
Impacts Per Minute (IPM)	1600
Max. Torque (ft-lb)	500



Styled for perfection and built to last!

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
851 Jupiter Park Lane / Jupiter, Florida 33458

www.AIRCAT.com

(800) 356-3392

FEATURE

- Low weight composite housing reduces weight to 1.13 kg.
- Reliable jumbo hammer mechanism delivers maximum power, while increasing reliability
- Patented "Silencing Technology" reduces the noise level to 85 dBA
- Patented grip has been ergonomically designed to perfectly fit the hand, providing unmatched comfort for the user
- Newly patented trigger mounted combined reverse and power management switch provides ultimate control and one-hand operation
- Provides ultimate reliability with the triple heat treated "alloy steel hammer mechanism parts and anvil

SPECIFICATIONS

Maximum torque (Nm): 750
Square drive (in.): 1/2
Impact per minute: 1650
Free speed (rpm): 9,000
Bolt capacity (mm): 15

Weight (kg): 1.13
Length (mm): 107.95
Vibration level M/ Sec2: 9.9
Air Consistency (CFM): 8
Recommended hose size (in.): 3/8



NITROCAT
X-TRIME
POWER



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1058-VXL

Compact Impact Wrench

FEATURE

- Provides 750 nm maximum torque.
- Vibrotherm drive® impact wrenches incorporate the completely new aircat design impact wrench mechanism (patent pending).
- The new mechanism reduces vibration levels by between 30%-40% and increases the life of the mechanism by 50%.
- The latest patented aircat muffler system produces the characteristic aircat unmatched low noise levels;
- The patented grip design provides the operator the ultimate comfort.
- Investment into tooling and materials and a triple injection molding processes enable aircat to produce cosmetic designs that are unmatched in the industry.
- "three year warranty".

SPECIFICATIONS

Maximum torque (Nm): 750
Square drive (in.): 1/2
Impact per minute: 1700
Free speed (rpm): 9,000
Bolt capacity (mm): 15

Weight (kg): 1.27
Length (mm): 111.76
Vibration level M/ Sec2: 4.3
Air Consistency (CFM): 8
Recommended hose size (in.): 3/8



VIBROTHERM
by AIRCAT DRIVE

Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1059-VXL

Compact Impact Wrench

FEATURE

- Provides 750 nm maximum torque.
- Vibrotherm drive® impact wrenches incorporate the completely new aircat design impact wrench mechanism (patent pending).
- The new mechanism reduces vibration levels by between 30%-40% and increases the life of the mechanism by 50%.
- The latest patented aircat muffler system produces the characteristic aircat unmatched low noise levels.
- The patented grip design provides the operator the ultimate comfort.
- Investment into tooling and materials and a triple injection molding processes enable aircat to produce cosmetic designs that are unmatched in the industry.
- "Three year warranty".

SPECIFICATIONS

Maximum torque (Nm): 750
Square drive (in.): 3/8
Impact per minute: 1700
Free speed (rpm): 9,000
Bolt capacity (mm): 15

Weight (kg): 1.27
Length (mm): 111.76
Vibration level M/ Sec2: 4.3
Air Consistency (CFM): 8
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURES

- Provides 550 ft-lb maximum torque
- Low weight composite housing reduces weight to 2.5 Lbs.
- Reliable jumbo hammer mechanism delivers maximum power, while increasing reliability
- Patented "silencing technology" reduces the noise level to 85 dba
- Patented grip has been ergonomically designed to perfectly fit the hand, providing unmatched comfort for the user
- New patented trigger mounted combined reverse & power management switch provides ultimate control and one-hand operation
- Triple heat treated ni-cr-mo alloy steel hammer mechanism parts and anvil provide ultimate reliability

SPECIFICATIONS

Square Drive (in.)	3/8
Air Cons. (CFM)	8
Bolt Capacity (in.)	9/16
Air Inlet (in.) NPT/BSP	1/4
Rec. Hose Size (in.)	3/8
Weight (lbs.)	2.5
Length (in.)	4.25
Free Speed (RPM)	9000
Impacts Per Minute (IPM)	1650
Max. Torque (ft-lb)	550



Styled for perfection and built to last!

FEATURE

- Provides 1080 nm maximum torque and 1355 nm of loosening torque.
- Hard hitting twin hammer mechanism delivers maximum power.
- Grip is ergonomically designed to perfectly fit the hand, providing unmatched comfort for the user.
- Cross bolt forward/reverse and power management control.
- Triple heat treated ni-cr-mo alloy steel hammer mechanism parts and anvil provide ultimate reliability.

SPECIFICATIONS

Maximum torque (Nm): 1080
Square drive (in.): 1/2
Impact per minute: 1600
Free speed (rpm): 9,000
Bolt capacity (mm): 13

Weight (kg): 2.5
Length (mm): 182.8
Vibration level M/ Sec2: 12.5
Air Consistency (CFM): 8
Recommended hose size (in.): 3/8



Performance Proven Products

FEATURE

- Provides 1090 nm maximum torque.
- Refined design twin hammer increases blow.
- Frequency and blow efficiency.
- Very fast torque development.
- 9,000 rpm free speed provides fast run-down.
- Ergonomically designed grip provides maximum operating comfort.
- Six position power management switch in back cap provides ultimate control.
- Great balance and handling comfort.
- Brushed aluminum housing finish.

SPECIFICATIONS

Maximum torque (Nm): 1090
Square drive (in.): 1/2
Impact per minute: 1200
Free speed (rpm): 9,000
Bolt capacity (mm): 15

Weight (kg): 2.20
Length (mm): 177.80
Vibration level M/ Sec2: 13.5
Air Consistency (CFM): 8
Recommended hose size (in.): 3/8



1450-2
2" Ext. Anvil

Performance Proven Products



1150

Impact Wrench

FEATURE

- Provides 1700 nm maximum torque.
- Most powerful 1/2" impact in it's class.
- Hard hitting twin hammer mechanism.
- Durable composite housing.
- Patented ergonomically designed handle.
- Patented quiet tuned exhaust (86 decibels).
- Patented easy operation flip lever forward and reverse.

SPECIFICATIONS

Maximum torque (Nm): 1250
Square drive (in.): 1/2
Impact per minute: 1400
Free speed (rpm): 9,000
Bolt capacity (mm): 15

Weight (kg): 2.04
Length (mm): 190.50
Vibration level M/ Sec2: 8.1
Air Consistency (CFM): 8
Recommended hose size (in.): 3/8

KILLER TORQUE



Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURES

- Provides 950 ft-lb maximum torque and 1,300 ft-lb of loosening torque
- VIBROTHERM DRIVE® impact wrenches incorporates the new patented AIRCAT design impact wrench mechanism
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%
- The latest patented AIRCAT muffler system provides the AIRCAT's unmatched low noise levels (86 dBA)
- The patented grip design provides the customary AIRCAT® operator comfort

SPECIFICATIONS

Length (in.)	6.4
Width (in.)	2.85
Height (in.)	7.65
Weight (lbs.)	4.5
Bolt Capacity (in.)	9/16
Loosening Torque (ft-lbs)	1300
Working Torque (ft-lb)	145-665
Air Cons. (CFM)	8
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4 NPT
Vibration Level (m/sec ²)	7.7
Noise Level d(B)A	86
Square Drive (in.)	1/2



Styled for perfection
and built to last!

Free Speed (RPM)	7500
Impacts Per Minute (IPM)	1400
Max. Torque (ft-lb)	950

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
1660 Silver Beach Road-Suite 100 Lake Park, FL 33409

www.AIRCAT.com

(800) 356-3392



1125

Super Duty Magnesium
Impact Wrench

FEATURE

- Provides 1355nm maximum torque and 1694nm of loosening torque.
- Sets industry standard for weight and size in class.
- Hard hitting twin hammer mechanism.
- Durable composite housing.
- Patented ergonomically designed handle.
- Patented quiet tuned exhaust (86 dba).
- Patented easy operation flip lever forward and reverse.

SPECIFICATIONS

Maximum torque (Nm): 1694
Square drive (in.): 1/2
Impact per minute: 1600
Free speed (rpm): 8,500
Bolt capacity (mm): 15

Weight (kg): 1.72
Length (mm): 180,34
Vibration level M/ Sec2: 8.1
Air Consistency (CFM): 8
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1600-TH-A

“super Duty” Impact Wrench

FEATURE

- Provides 1900 nm maximum torque.
- Hard hitting “super duty” twin hammer mechanism.
- Best suited for bus/large automotive use, large agricultural service vehicles & large bolt assembly.
- Patented ergonomically designed handle.
- Patented quiet tuned exhaust (86 decibels).
- Patented easy operation flip lever forward and reverse.
- Combined through hole and friction ring socket retainer.

SPECIFICATIONS

Maximum torque (Nm): 1900
Square drive (in.): 3/4
Impact per minute: 900
Free speed (rpm): 4,500
Bolt capacity (mm): 22

Weight (kg): 3.67
Length (mm): 234.95
Vibration level M/ Sec2: 7.4
Air Consistency (CFM): 10
Recommended hose size (in.): 1/2



Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1600-TH-A1

Composite Impact Wrench

FEATURE

- Provides 1900 nm maximum torque.
- Hard hitting "super duty" twin hammer mechanism.
- Best suited for bus/large automotive use, large agricultural service Vehicles & large bolt assembly.
- Patented ergonomically designed handle.
- Patented quiet tuned exhaust (86 decibels).
- Patented easy operation flip lever forward and reverse.
- Combined through hole and friction ring socket retainer.

SPECIFICATIONS

Maximum torque (Nm): 1900
Square drive (in.): 1
Impact per minute: 1100
Free speed (rpm): 4500
Bolt capacity (mm): 32

Weight (kg): 3.74
Length (mm): 234.95
Vibration level M/ Sec2: 7.4
Air Consistency (CFM): 10
Recommended hose size (in.): 1/2



Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

AIRCAT

PNEUMATIC TOOLS

1777

“super Duty” Impact Wrench

FEATURE

- Provides 1900 nm maximum torque.
- Refined design twin hammer increases blow efficiency and doubles hammer mechanism life.
- Hammer parts are made from triple heat treated ni-cr-mo alloy steel for ultimate reliability.
- Improved design ergonomic grip for maximum operating comfort.
- Very fast torque development.
- Combined six position power management and reverse knob for ultimate control.

SPECIFICATIONS

Maximum torque (Nm): 1900
Square drive (in.): 3/4
Impact per minute: 1600
Free speed (rpm): 9000
Bolt capacity (mm): 13

Weight (kg): 3.4
Length (mm): 9779
Vibration level M/ Sec2: 12.5
Air Consistency (CFM): 60
Recommended hose size (in.): 3/8



Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

AIRCAT

PNEUMATIC TOOLS

1778-VXL

Impact Wrench

FEATURE

- Provides 2300 nm maximum torque.
- Vibrotherm drive® impact wrenches incorporate the completely new aircat design impact wrench mechanism (patent pending).
- The new mechanism reduces vibration levels by between 30%-40% and increases the life of the mechanism by 50%.
- The latest patented aircat muffler system produces the.
- Characteristic aircat unmatched low noise levels.
- The patented grip design provide the customary aircat operator comfort.
- Investment into tooling and materials and a triple injection.
- Molding processes enables aircat to produce cosmetic designs that are unmatched in the industry.
- "three year warranty"

SPECIFICATIONS

Maximum torque (Nm): 1290
Square drive (in.): 3/4
Impact per minute: 1400
Free speed (rpm): 7,500
Bolt capacity (mm): 19

Weight (kg): 2.90
Length (mm): 203.20
Vibration level M/ Sec2: 6.5
Air Consistency (CFM): 8
Recommended hose size (in.): 1/4



VIBROTHERM
by AIRCAT DRIVE

Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURES

- Provides 1,800 ft-lb maximum torque and 2,000 ft-lb of loosening torque
- Low maintenance pin-less hammer provides ultimate reliability and added hitting power
- Features enlarged inner cavity of rotating D handle grip
- Combined forward/reverse and power management switch
- Triple heated Ni-Cr-Mo alloy steel hammer mechanism parts and anvil provides ultimate reliability
- Combined through hole and friction ring socket retainer

SPECIFICATIONS

Length (in.)	15.5
Width (in.)	8.5
Height (in.)	7.25
Weight (lbs.)	23.2
Bolt Capacity (in.)	1-1/4
Loosening Torque (ft-lbs)	2000
Working Torque (ft-lb)	270-1260
Air Cons. (CFM)	12
Rec. Hose Size (in.)	1/2
Air Inlet (in.) NPT/BSP	1/2 NPT
Vibration Level (m/sec ²)	9.6
Noise Level d(B)A	109
Square Drive (in.)	1



Styled for perfection
and built to last!

Free Speed (RPM)	5000
Impacts Per Minute (IPM)	1600
Max. Torque (ft-lb)	1800

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
1660 Silver Beach Road-Suite 100 Lake Park, FL 33409

www.AIRCAT.com

(800) 356-3392



1992

EXTENDED Straight
Impact Wrench

FEATURE

- Provides 2440 nm maximum torque and 2700 nm of loosening torque.
- Low maintenance pin-less hammer provides ultimate reliability and added hitting power.
- Combined forward/reverse and power management switch.
- Triple heated ni-cr-mo alloy steel hammer mechanism parts and anvil provides ultimate reliability.
- Combined through hole and friction ring socket retainer.

SPECIFICATIONS

Maximum torque (Nm): 2440
Square drive (in.): 1X8
Impact per minute: 1600
Free speed (rpm): 5000
Bolt capacity (mm): 25.4

Weight (kg): 11.79
Length (mm): 558.80
Vibration level M/ Sec2: 12.1
Air Consistency (CFM): 12
Recommended hose size (in.): 1/2



AC1992-1
Short anvil
available

Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1900-A

Extended "super Duty"
Impact Wrench

FEATURE

- Provides 2580 nm maximum torque.
- Unique low wear pinless hammer.
- Aluminum housing with rubber over mold for increased protection.
- Ergonomic trigger with rubber inlay for comfort.
- Rugged bolt-on side assist handle can be repositioned on right or left.
- Triple heat treated ni-cr-mo alloy steel hammer mechanism parts and anvil provide ultimate reliability.
- Combined through hole and friction ring socket retainer.

SPECIFICATIONS

Maximum torque (Nm): 2580
Square drive (in.): 1X8
Impact per minute: 1600
Free speed (rpm): 5,500
Bolt capacity (mm): 32

Weight (kg): 11.79
Length (mm): 558.80
Vibration level M/ Sec2: 12.1
Air Consistency (CFM): 12
Recommended hose size (in.): 1/2



AC1900-A-1
Short anvil
available

Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

AIRCAT

PNEUMATIC TOOLS

1900A-1

Extended "super Duty"
Impact Wrench

FEATURE

- Provides 2580 nm maximum torque.
- Unique low wear pinless hammer.
- Aluminum housing with rubber over mold for increased protection.
- Ergonomic trigger with rubber inlay for comfort.
- Rugged bolt-on side assist handle can be repositioned on right or left.
- Triple heat treated ni-cr-mo alloy steel hammer mechanism parts and anvil provide ultimate reliability.
- Combined through hole and friction ring socket retainer.

SPECIFICATIONS

Maximum torque (Nm): 2580	Weight (kg): 10.97
Square drive (in.): 1	Length (mm): 393.70
Impact per minute: 1600	Vibration level M/ Sec2: 12.0
Free speed (rpm): 5,500	Air Consistency (CFM): 12
Bolt capacity (mm): 32	Recommended hose size (in.): 1/2



Perfectly stylised and built for eternity

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURES

- Provides 2,000 ft-lb maximum torque and 2,500 ft-lb of loosening torque
- Two jaw clutch provides unparalleled torque output and increases the life of the hammer beyond other impact mechanisms
- The two jaw clutch does not waste energy. This combined with the precision air motor dramatically reduces air consumption over other 1" impact wrenches to 24.5 CFM free running and 6 average
- Designed for fleet and off road vehicle service and steel erection
- Steel hammer case and heavy duty cast housing handle provide ultimate reliability
- Combined through hole and friction ring socket retainer

SPECIFICATIONS

Length (in.)	11
Width (in.)	5
Height (in.)	10.5
Weight (lbs.)	24
Bolt Capacity (in.)	1.25
Loosening Torque (ft-lbs)	2500
Working Torque (ft-lb)	300-1400
Air Cons. (CFM)	6
Rec. Hose Size (in.)	1/2
Air Inlet (in.) NPT/BSP	1/2 NPT
Vibration Level (m/sec ²)	12.6



Styled for perfection
and built to last!

Noise Level d(B)A	102
Square Drive (in.)	1
Free Speed (RPM)	4200
Impacts Per Minute (IPM)	1200
Max. Torque (ft-lb)	2000



1870-P

“Super Duty” Pistol
Impact Wrench

FEATURE

- Provides 2850 nm maximum torque.
- Unmatched power to weight ratio - weighs only 5.87 kg.
- 1870-p has low weight impact-resistant housing.
- Features combined friction-ring and through-hole socket retainers.
- Cranked side handle design avoids operators hand getting too close to work area.

SPECIFICATIONS

Maximum torque (Nm): 2850

Square drive (in.): 1

Impact per minute: 1400

Free speed (rpm): 7500

Bolt capacity (mm): 32

Weight (kg): 5.87

Length (mm): 271.78

Vibration level M/ Sec2: 8.6

Air Consistency (CFM): 7.5

Recommended hose size (in.): 1/2



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURES

- Provides 1,900 ft-lb maximum torque and 2,100 ft-lb of loosening torque
- Unmatched power to weight ratio for 6" Extended Anvil Impact ONLY 14.8 lbs
- Low weight impact-resistant housing
- Features combined friction-ring and through-hole socket retainers
- Offset side handle design prevents operators hand getting too close to work area

SPECIFICATIONS

Length (in.)	16
Width (in.)	7.3
Height (in.)	9.8
Weight (lbs.)	14.8
Free Speed (BPM)	7500
Bolt Capacity (in.)	1.25
Loosening Torque (ft-lbs)	2300
Working Torque (ft-lb)	315-1470
Air Cons. (CFM)	10
Rec. Hose Size (in.)	1/2
Air Inlet (in.) NPT/BSP	1/2 NPT
Vibration Level (m/sec ²)	8.6
Noise Level d(B)A	96



Styled for perfection
and built to last!

Square Drive (in.)	1
Free Speed (RPM)	7500
Max. Torque (ft-lb)	2100

FEATURE

- Provides 2850 nm maximum torque.
- Unmatched power to weight ratio.
- Exhaust can be located at either the top or bottom of tool.
- Rubber handle grips and rubberized trigger inserts for ultimate comfort.
- Combined friction-ring and through-hole socket retainers.

SPECIFICATIONS

Maximum torque (Nm): 2850	Weight (kg): 9.38
Square drive (in.): 1X7	Length (mm): 482.60
Impact per minute: 1600	Vibration level M/ Sec2: 8.8
Free speed (rpm): 6000	Air Consistency (CFM): 8
Bolt capacity (mm): 32	Recommended hose size (in.): 1/2



AC1991-1 2" Short anvil available

Perfectly stylised and built for eternity



1991-1

Extended "super Duty"
Impact Wrench

FEATURE

- Provides 2850 nm maximum torque.
- Unmatched power to weight ratio.
- Exhaust can be located at either the top or bottom of tool.
- Rubber handle grips and rubberized trigger inserts for ultimate comfort.
- Combined friction-ring and through-hole socket retainers.

SPECIFICATIONS

Maximum torque (Nm): 2850
Square drive (in.): 1
Impact per minute: 1600
Free speed (rpm): 6000
Bolt capacity (mm): 32

Weight (kg): 7.57
Length (mm): 327.66
Vibration level M/ Sec2: 8.8
Air Consistency (CFM): 8
Recommended hose size (in.): 1/2



AC1991-1 2" Short anvil available

Perfectly stylised and built for eternity

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1993-1-VXL

Vibrotherm Impact Wrench

FEATURE

- Provides 3110 nm of maximum torque.
- Vibrotherm drive® impact wrenches incorporates the new patented aircat design impact wrench mechanism.
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%.
- 6,000 rpm free speed.
- Unmatched power-to-weight ratio.
- Rubber handle grip and rubberized trigger inserts for ultimate comfort.
- Combined friction-ring and through-hole socket retainer.
- Materials, and the triple injection molding processes enables aircat to produce cosmetic designs that are unmatched in the industry.

SPECIFICATIONS

Maximum torque (Nm): 3120

Weight (kg): 8.38

Square drive (in.): 1X2

Length (mm): 340.36

Impact per minute: 950

Vibration level M/ Sec2: 12.7

Free speed (rpm): 6000

Air Consistency (CFM): 10

Bolt capacity (mm): 32

Recommended hose size (in.): 1/2



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1993-VXL

Vibrotherm Impact Wrench

FEATURE

- Provides 3110 nm of maximum torque.
- Vibrotherm drive® impact wrenches incorporates the new patented aircat design impact wrench mechanism.
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%.
- 6,000 rpm free speed.
- Unmatched power-to-weight ratio.
- Rubber handle grip and rubberized trigger inserts for ultimate comfort.
- Combined friction-ring and through-hole socket retainers.
- Materials and the triple injection molding processes enable aircat to produce cosmetic designs that are unmatched in the industry.

SPECIFICATIONS

Maximum torque (Nm): 3120
Square drive (in.): 1X7
Impact per minute: 950
Free speed (rpm): 6000
Bolt capacity (mm): 32

Weight (kg): 9.16
Length (mm): 474.98
Vibration level M/ Sec2: 12.7
Air Consistency (CFM): 10
Recommended hose size (in.): 1/2



Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



1994

EXTENDED "SUPER DUTY"
Straight Impact Wrench

FEATURE

- Provides 3120 nm maximum torque and 3400 nm of loosening torque.
- Low maintenance pin-less hammer provides ultimate reliability and added hitting power.
- Combined forward/reverse and power management switch.
- Triple heat treated alloy steel hammer cage and anvil.
- Rugged construction with reliable bolt-on assist side handle.
- Hammer case can be repositioned for the side handle to be on right or left side.
- Brushed aluminum motor housing.
- Aircat's most reliable 1" impact wrench.
- Combined through hole and friction ring socket retainer.

SPECIFICATIONS

Maximum torque (Nm): 3120
Square drive (in.): 1X8
Impact per minute: 1100
Free speed (rpm): 4500
Bolt capacity (mm): 25.4

Weight (kg): 15.87
Length (mm): 660.40
Vibration level M/ Sec2: 12.0
Air Consistency (CFM): 12
Recommended hose size (in.): 1/2



Performance Proven Products

+44 1494 883300
AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM