



6700-8GCV

Geared 5mm Orbital Sander
Central Vac

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Low vibration level 2.5m/sec²
- Advanced silencing technology reduces noise level to 78 d(B)A
- Low average air consumption of 3.0 CFM
- Ergonomic throttle lever design increases comfort

SPECIFICATIONS

Free speed (rpm): 900
Pad Type: Hook & Look
Pad/Bonnet Size (in.): 8
Weight (kg): 1.58

Length (mm): 304.80
Vibration Levels M/sec²: 2.5
Air Consistency (CFM): 3
Noise Level d(B)A: 78



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6700-6GCV

Geared 5mm Orbital Sander
Central Vac

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Low vibration level 2.5m/sec²
- Advanced silencing technology reduces noise level to 78 d(B)A
- Low average air consumption of 3.0 CFM
- Ergonomic throttle lever design increases comfort

SPECIFICATIONS

Free speed (rpm): 900
Pad Type: Hook & Look
Pad/Bonnet Size (in.): 8
Weight (kg): 1.54

Length (mm): 279.40
Vibration Levels M/sec²: 2.5
Air Consistency (CFM): 3
Noise Level d(B)A: 78



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



AC6700-1-332

Non Vac Palm Sander

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec²
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Free speed (rpm): 11,000
Pad Type: Hook & Loop
Pad/Bonnet Size (in.): 6
Weight (kg): 0.77

Length (mm): 170.18
Vibration Levels M/sec²: 0.8
Air Consistency (CFM): 1.6
Noise Level d(B)A: 75



Perfectly stylised and built for eternity

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURE

- 10,000 rpm
- 4.76 mm orbit
- Low weight (1 kg) and low air consumption (2.5 cfm average)
- Lubrication free air motor with patented double sealing to prevent dust contamination
- Isolated motor design reduces vibration to 1.8 m/sec²
- Internal silencing system reduces noise level to 82 dba
- Built-in thumb operated speed regulator for instant control
- Rubberized comfort palm grip
- Low profile only 3-3/4" high

SPECIFICATIONS

Pad/Belt Size (in): 6
Spindle Thread Size (in): 3/8x24
Gears: Direct Drive
Exhaust: Rear
Orbit Off-set (mm): 4.46

Weight (kg): 1.0
Length (mm): 266,70
Vibration Levels M/sec²: 1.8
Air Consistency (CFM): 2.5
Recommended hose size (in.): 3/8



Perfectly stylised and built for eternity

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec2
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Free speed (rpm): 900
Pad Type: Hook & Loop
Pad/Bonnet Size (in.): 6
Weight (kg): 1.13

Length (mm): 195.00
Vibration Levels M/sec2: 0.8
Air Consistency (CFM): 1.6
Noise Level d(B)A: 75



Performance Proven Products

FEATURES

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec²
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Pad/Bonnet Size (in.)	5
Orbit (in)	3/16
Pad Type	Hook & Loop
No. Vacuum Pad Holes	0
Free Speed (RPM)	11,000
Weight (lbs.)	2.0
Length w/ Pad Fitted (in.)	6.7
Width w/ Pad Fitted (in.)	5.0
Height w/ Pad Fitted (in.)	4.3
Noise Level d(B)A	75
Vibration Level (m/sec ²)	0.8
Air Cons. (CFM)	1.6
Air Inlet (in.) NPT/BSP	1/4



Styled for perfection and built to last!



6700-6-336

Non Vac Orbital Palm Sander

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec2
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Free speed (rpm): 11,000
Pad Type: Hook & Loop
Pad/Bonnet Size (in.): 6
Weight (kg): 0.90

Length (mm): 172.72
Vibration Levels M/sec2: 0.8
Air Consistency (CFM): 1.6
Noise Level d(B)A: 75



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6700-6-332

Non Vac Orbital Palm Sander

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec2
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Free speed (rpm): 11,000
Pad Type: Hook & Loop
Pad/Bonnet Size (in.): 6
Weight (kg): 0.90

Length (mm): 172.72
Vibration Levels M/sec2: 0.8
Air Consistency (CFM): 1.6
Noise Level d(B)A: 75



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6700-5-336CV

ORBITAL PALM SANDER-CENTRAL VACUUM

FEATURES

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec²
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Pad/Bonnet Size (in.)	5
Orbit (in)	3/16
Pad Type	Hook & Loop
No. Vacuum Pad Holes	6
Free Speed (RPM)	11,000
Weight (lbs.)	2.0
Length w/ Pad Fitted (in.)	8.4
Width w/ Pad Fitted (in.)	5.0
Height w/ Pad Fitted (in.)	4.3
Noise Level d(B)A	75
Vibration Level (m/sec ²)	0.8
Air Cons. (CFM)	1.6
Air Inlet (in.) NPT/BSP	1/4



Styled for perfection and built to last!

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
851 Jupiter Park Lane / Jupiter, Florida 33458

www.AIRCAT.com

(800) 356-3392



6700-6-336CV

Composite 5mm Orbital Palm
Sander Central Vac

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec2
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Free speed (rpm): 11,000
Pad Type: Hook & Loop
Pad/Bonnet Size (in.): 6
Weight (kg): 0.90

Length (mm): 213,36
Vibration Levels M/sec²: 0.8
Air Consistency (CFM): 1.6
Noise Level d(B)A: 75



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6700-6-332CV

Central Vac Orbital Palm Sander

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec2
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Free speed (rpm): 11,000
Pad Type: Hook & Loop
Pad/Bonnet Size (in.): 6
Weight (kg): 0.90

Length (mm): 213.36
Vibration Levels M/sec²: 0.8
Air Consistency (CFM): 1.6
Noise Level d(B)A: 75



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6700-6-336SV

Composite 5mm Orbital Palm
Sander Hose & Bag

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec2
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Free speed (rpm): 11,000
Pad Type: Hook & Loop
Pad/Bonnet Size (in.): 8
Weight (kg): 0.90

Length (mm): 205.74
Vibration Levels M/sec2: 0.8
Air Consistency (CFM): 1.6
Noise Level d(B)A: 75



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



6700-6-332SV

Composite 2.5mm Orbital Palm Sander Hose & Bag

FEATURE

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Patented "anti vibration" motor design reduces vibration level to 0.8m/sec2
- Advanced silencing technology reduces noise level to 75 d(B)A
- Smooth design throttle lever and ergonomic grip provide unmatched comfort
- AIRCAT technology reduces average air consumption to 1.6 CFM

SPECIFICATIONS

Free speed (rpm): 11,000
Pad Type: Hook & Loop
Pad/Bonnet Size (in.): 6
Weight (kg): 0.90

Length (mm): 205.74
Vibration Levels M/sec2: 0.8
Air Consistency (CFM): 1.6
Noise Level d(B)A: 75



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURES

- Pad type Hook and Loop / PSA
- Patented double sealed, lubrication free motor prevents dust contamination of the air motor and eliminates the need for oiling
- AIRCAT orbital sanders feature smooth design throttle lever and ergonomic grip providing unmatched comfort
- Patented anti vibration motor reduces vibration levels
- Low profile design

SPECIFICATIONS

Length (in.)	5.7
Width (in.)	3
Height (in.)	4.5
Weight (lbs.)	1.8
Pad/Bonnet Size (in.)	3
Pad Type	Hook & Loop
Exhaust	Rear
Pad Thread (in.)	1/4 X 20
Air Cons. (CFM)	1.6
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4 NPT
Vibration Level (m/sec ²)	0.8
Noise Level d(B)A	75



Styled for perfection
and built to last!

Free Speed (RPM)	11000
Orbit Off-set (in.)	3/32

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
1660 Silver Beach Road-Suite 100 Lake Park, FL 33409

www.AIRCAT.com

(800) 356-3392

FEATURES

- Pad type Hook and Loop
- Patented double sealed, lubrication free motor prevents dust contamination of the air motor and eliminates the need for oiling
- AIRCAT orbital sanders feature smooth design throttle lever and ergonomic grip providing unmatched comfort
- Patented anti vibration motor reduces vibration levels
- Low profile design

SPECIFICATIONS

Length (in.)	7.3
Width (in.)	3
Height (in.)	4.5
Weight (lbs.)	1.8
Pad/Bonnet Size (in.)	3
Pad Type	Hook & Loop
No. Vacuum Pad Holes	6
Exhaust	Rear
Pad Thread (in.)	1/4 X 20
Air Cons. (CFM)	1.6
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4 NPT
Vibration Level (m/sec ²)	0.8



Styled for perfection
and built to last!

Noise Level d(B)A	75
Free Speed (RPM)	11000
Orbit Off-set (in.)	3/32

FEATURE

- Features internal 1/8" orbital head for ultra-fine sanding and polishing
- The combined spindle-counter balance reduces vibration levels to 1.8 m/sec² and adds reliability
- Precision alloy steel spiral-bevel gears extend tool life
- Lambswool and sponge polishing bonnets/pads are also available separately
- The internal silencing system reduces noise levels to 78 dba
- Supplied complete with hook & loop 1.25" and 2" round and a triangular pad sanding discs for all three pads types are available separately in 120/180/320/600/1000/1500 grit sizes, sanding discs are packed as 10 pc.

SPECIFICATIONS

Free speed (rpm): 13,000
Pad/Bonnet Size (in): 1x2
Spindle Thread Size (in): 1/4
Orbit off-set (mm): 3.17

Weight (kg): 0.49
Length (mm): 154.94
Vibration Levels M/sec²: 1.8
Air Consistency (CFM): 2.5
Rec. Hose Size (in.): 3/8



Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURE

- Low weight composite housing
- Top mounted one-hand forward/reverse switch
- Feather speed control trigger
- Internal silencing system reduces noise level to (88 dba)
- Kit features blow mold storage tray, pistol grip sander, both 2" and 3" sanding pads as well as An assortments of 2" and 3" sand paper

SPECIFICATIONS

Free speed (rpm): 16,000

Pad/Belt Size (in): 5/16-24

Spindle Thread Size (in): 3/8x24

Weight (kg): 0.71

Length (mm): 132,08

Vibration Levels M/sec2: 3.3

Air Consistency (CFM): 2



Perfectly stylised and built for eternity

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM

FEATURE

- Low weight composite housing
- Top mounted one-hand forward/reverse switch
- Feather speed control trigger
- Internal silencing system reduces noise level to (88 dba)

SPECIFICATIONS

Free speed (rpm): 16,000

Pad/Belt Size (in): 5/16-24

Spindle Thread Size (in): 3/8x24

Weight (kg): 0.71

Length (mm): 132,08

Vibration Levels M/sec²: 3.3

Air Consistency (CFM): 2



Perfectly stylised and built for eternity

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM