

Nibbler

### **FEATURE**

- ullet 2,600 spm motor provides fast cutting action in steel up to 18 gauge.
- 6330 has the smallest cut radius of any nibbler at only 7.62 cm allowing clean cuts in tight corners.
- The "over sized" anvil and punch dramatically increases the reliability of these high wear parts.
- · Includes an additional punch.
- Composite handle and throttle lever design provide comfortable and convenient operation.

#### **SPECIFICATIONS**

Free speed (rpm): 2600 Motor (hp): 0.50 Cutting Capacity: 18 gauge Exhaust: Rear Weight (kg): 1.13 Length (mm): 177.80 Vibration level M/ Sec2: 7.7 Air Consistency (CFM): 3.5 Recommended hose size (in.): 3/8



**Performance Proven Products** 

C+44 1494 883300

#AIRCAT-TOOLS.COM

↑ UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



**Compact Needle Scaler** 

#### **FEATURE**

- 4,800 bpm.
- 1-1/4" stroke.
- · Low weight compact design.
- Durable steel housing.
- · Best for removal of rust, paint and scale on flat or irregular surfaces.

#### **SPECIFICATIONS**

Free speed (rpm): 4800 (BPM)

**Exhaust: Rear** 

Weight (kg): 1.31 Length (mm): 292.1

Air Consistency (CFM): 4

Recommended hose size (in.): 3/8



**Performance Proven Products** 

C+44 1494 883300

**AIRCAT-TOOLS.COM** 

↑ UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



**Low Vibration Air Saw** 

#### **FEATURE**

- 9,500 stroke/minute motor provides fast cutting action.
- The internal damping system reduces the vibration level to 2.5m/sec2. · Comes complete with 18, 24 and 32 teeth power saw blades.
- The metal blade retainer increases reliability.
- The rotational 360° rear exhaust muffler allows exhaust air to be directed as preferred.
- · Features a short overall length of only 8" and low a weight of only 1.13 lbs. Providing good work area access and comfortable operation.

#### **SPECIFICATIONS**

Free speed (rpm): 9500 Motor (hp): 0.45 Cutting Capacity: 3/16" Steel Plate - 18 Gauge Exhaust: Rear

Weight (kg): 0.51 Length (mm): 203.20 Vibration level M/ Sec2: 7.7 Air Consistency (CFM): 4 Recommended hose size (in.): 3/8



**Performance Proven Products** 

C+44 1494 883300

**\*\*AIRCAT-TOOLS.COM** 

**↑** UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM



**Reciprocating Air Saw** 

## **FEATURE**

- 5,000 spm.
- Dual-speed design for control.
- · Quick change blade design retainer for quick and easy blade Changes.
- · Accepts various types of reciprocating saw blades.
- Patented reciprocating crank mechanism motor.
- Capable of cutting 2.54 cm thick steel and steel pipe up to 7.62c.
- Rear exhaust.

## **SPECIFICATIONS**

Free speed (rpm): 5000 Motor (hp): 0.45 Cutting Capacity: 1/4" Thick Steel and Steel pipe up to 3" Exhaust: Rear

Weight (kg): 1.10 Length (mm): 309.88 Vibration level M/ Sec2: 7.7 Air Consistency (CFM): 3.5 Recommended hose size (in.): 3/8



**Performance Proven Products** 

C+44 1494 883300

& AIRCAT-TOOLS.COM

TUNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM