

### FEATURES

- 0.75 HP Motor for extra stall resistance
- Reliable planetary gear system
- Trigger mounted reverse switch for convenient change of direction
- Contoured composite grip for comfort
- Best for: Intermittent general drilling and MRO

### SPECIFICATIONS

Motor (HP)	.75
Motor (kW)	0.51
Speed (RPM)	450
Exhaust	Handle
Chuck (in.)	1/2
Weight (lbs.)	3.0
Weight (kg.)	1.40
Length (in.)	9.00
Length (mm)	220.5
Air Inlet (in.)	1/4
Rec. Hose Size (in.)	3/8
Air Cons. (cfm)	14
Avg. Air Cons (cfm)	3.5



## Air Tools for Industry



### FEATURES

- 0.75 HP Motor for extra stall resistance
- Reliable planetary gear system
- Trigger mounted reverse switch for convenient change of direction
- Contoured composite grip for comfort
- Best for: Intermittent general drilling and MRO

### SPECIFICATIONS

Motor (HP)	.75
Motor (kW)	0.51
Speed (RPM)	700
Exhaust	Handle
Chuck (in.)	1/2
Weight (lbs.)	3.0
Weight (kg.)	1.40
Length (in.)	9.00
Length (mm)	220.5
Air Inlet (in.)	1/4
Rec. Hose Size (in.)	3/8
Air Cons. (cfm)	14
Avg. Air Cons (cfm)	3.5



## Air Tools for Industry





### FEATURES

- 0.65 HP Motor for extra stall resistance
- Double injection ergonomically advanced housing and grip
- Variable speed trigger with reverse on both sides
- Patented silencer reduces noise to 83 dBA
- Precision machined planetary gears with needle bearings
- Steel gear case for added durability
- Best for: Heavy duty continuous drilling

### SPECIFICATIONS

Motor (HP)	0.75
Motor (kW)	0.51
Speed (RPM)	800
Exhaust	Handle
Chuck (in.)	1/2"
Weight (lbs.)	2.9
Weight (kg.)	1.3
Length (in.)	8.50
Length (mm)	216
Air Inlet (in.)	1/4
Rec. Hose Size (in.)	3/8
Air Cons. (cfm)	14
Avg. Air Cons (cfm)	3.5



## Air Tools for Industry



**FEATURES**

- 0.9 HP Motor for ultimate stall resistance
- Fully caged gears with needle bearings for ultimate reliability
- Ported throttle valve for ultimate control and reliability
- Through handle exhaust with built-in silencing system
- Advanced ergonomically designed handle with "Softouch" coating offers ultimate comfort and reduced vibration
- Jacobs® industrial chuck for accuracy and durability
- Assist handle for added control
- Best for: Continuous drilling in high volume applications

**SPECIFICATIONS**

Motor (HP)	0.9
Motor (kW)	0.66
Speed (RPM)	500
Exhaust	Handle
Chuck (in.)	1/2"
Weight (lbs.)	3.2
Weight (kg.)	1.5
Length (in.)	9.50
Length (mm)	241
Air Inlet (in.)	1/4
Rec. Hose Size (in.)	3/8
Air Cons. (cfm)	18.4
Avg. Air Cons (cfm)	4.6



Air Tools for Industry





### FEATURES

- 0.8 HP Motor for ultimate stall resistance
- Fully caged gears with needle bearings for ultimate reliability
- Ported throttle valve for ultimate control and reliability
- Through handle exhaust with built-in silencing system
- Advanced ergonomically designed handle with "Softouch" coating offers ultimate comfort and reduced vibration
- Jacobs® industrial chuck for accuracy and durability
- Assist handle for added control
- Best for: Continuous drilling in high volume applications

### SPECIFICATIONS

Motor (HP)	0.8
Motor (kW)	0.59
Speed (RPM)	400
Exhaust	Handle
Chuck (in.)	1/2"
Weight (lbs.)	3.2
Weight (kg.)	1.5
Length (in.)	9.50
Length (mm)	241
Air Inlet (in.)	1/4
Rec. Hose Size (in.)	3/8
Air Cons. (cfm)	18.4
Avg. Air Cons (cfm)	4.6



## Air Tools for Industry



# UT8897

1/4" Pistol Drill

- Chuck Type Chuck & Key
- Chuck Size 1/4"
- Motor Power 0.90 HP
- Free Speed 20,000 RPM
- Air Cons 4.6 CFM
- Sound 83 dB (a)
- Vibration 3.6 m/sec<sup>2</sup>
- Length 193 mm
- Weight 0.9 kg
- Air Inlet 1/4" BSP



+ 44 (1) 494 883300  
sales@ut-tools.com



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM

**FEATURES**

- 0.8 HP Motor for ultimate stall resistance
- Fully caged gears with needle bearings for ultimate reliability
- Ported throttle valve for ultimate control and reliability
- Through handle exhaust with built-in silencing system
- Best for: high volume assembly

**SPECIFICATIONS**

Motor (HP)	0.8
Motor (kW)	0.59
Torque Range (in. lb.)	102
Speed (RPM)	1,800
Exhaust	Handle
Chuck (in.)	1/4" Hex Q.C.
Weight (lbs.)	2.1
Weight (kg.)	1.0
Length (in.)	7.75
Length (mm)	197
Air Inlet (NPT)	1/4
Rec. Hose (I.D. in.)	3/8
Air Cons. (cfm)	18.4
Avg. Air Cons (cfm)	4.6
Rec. Pressure	90 psi -6.2 bar



Air Tools for Industry





### FEATURES

- 0.75 HP Motor for extra stall resistance
- Reliable planetary gear system
- Trigger mounted reverse switch for convenient change of direction
- Contoured composite grip for comfort
- Best for: Intermittent general drilling and MRO

### SPECIFICATIONS

Motor (HP)	.75
Motor (kW)	0.51
Speed (RPM)	1,800
Exhaust	Handle
Chuck (in.)	3/8
Weight (lbs.)	2.5
Weight (kg.)	1.00
Length (in.)	7.00
Length (mm)	165
Air Inlet (in.)	1/4
Rec. Hose Size (in.)	3/8
Air Cons. (cfm)	14
Avg. Air Cons (cfm)	3.5



## Air Tools for Industry





### FEATURES

- 0.75 HP Motor for extra stall resistance
- Double injection ergonomically advanced housing and grip
- Variable speed trigger with reverse on both sides
- Patented silencer reduces noise to 83 dBA
- Precision machined planetary gears with needle bearings
- Steel gear case for added durability
- Best for: Heavy duty continuous drilling

### SPECIFICATIONS

Motor (HP)	.75
Motor (kW)	0.51
Speed (RPM)	1,800
Exhaust	Handle
Chuck (in.)	3/8
Weight (lbs.)	2.4
Weight (kg.)	1.1
Length (in.)	7.00
Length (mm)	178
Air Inlet (in.)	1/4
Rec. Hose Size (in.)	3/8
Air Cons. (cfm)	14
Avg. Air Cons (cfm)	3.5



## Air Tools for Industry



### FEATURES

- 0.9 HP Motor for ultimate stall resistance
- Fully caged gears with needle bearings for ultimate reliability
- Ported throttle valve for ultimate control and reliability
- Through handle exhaust with built-in silencing system
- Advanced ergonomically designed handle with "Softouch" coating offers ultimate comfort and reduced vibration
- Jacobs® industrial chuck for accuracy and durability
- Reversible models are ideal for reaming and rivet removal
- Best for: Continuous drilling in high volume applications

### SPECIFICATIONS

Motor (HP)	0.9
Motor (kW)	0.66
Gear Ratio	N/A
Speed (RPM)	2,600
Exhaust	Handle
Chuck (in.)	3/8"
Weight (lbs.)	2.1
Weight (kg.)	1.0
Length (in.)	7.75
Length (mm)	197
Air Inlet (NPT)	1/4
Rec. Hose (I.D. in.)	3/8"
Air Cons. (cfm)	18.4
Avg. Air Cons (cfm)	4.6
Rec. Pressure	90 psi-6.2 bar



## Air Tools for Industry





### FEATURES

- 0.9 HP Motor for ultimate stall resistance
- Fully caged gears with needle bearings for ultimate reliability
- Ported throttle valve for ultimate control and reliability
- Through handle exhaust with built-in silencing system
- Advanced ergonomically designed handle with "Softouch" coating offers ultimate comfort and reduced vibration
- Jacobs® industrial chuck for accuracy and durability
- Reversible models are ideal for reaming and rivet removal
- Best for: Continuous drilling in high volume applications

### SPECIFICATIONS

Motor (HP)	0.8
Motor (kW)	0.59
Gear Ratio	N/A
Speed (RPM)	1,800
Exhaust	Handle
Chuck (in.)	3/8"
Weight (lbs.)	2.1
Weight (kg.)	1.0
Length (in.)	7.75
Length (mm)	197
Air Inlet (NPT)	1/4
Rec. Hose (I.D. in.)	3/8"
Air Cons. (cfm)	18.4
Avg. Air Cons (cfm)	4.6
Rec. Pressure	90 psi-6.2 bar



## Air Tools for Industry



# UT5742D

3/8" Straight Drill chuck and key

- Chuck Type Chuck & Key
- Chuck Size 3/8"
- Free Speed 2600 RPM
- Air Cons 4 CFM
- Sound 79 dB (a)
- Vibration 2.0 m/sec<sup>2</sup>
- Length 235 mm
- Weight 1.1 kg
- Air Inlet 1/4" BSP



+ 44 (1) 494 883300  
sales@ut-tools.com



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM





# **UT5825-3/8K**

3/8" Reversible Drill Keyless

- Chuck Type Keyless
- Chuck Size 3/8"
- Motor Power 0.40 HP
- Free Speed 1800 RPM
- Air Cons 4 CFM
- Sound 91 dB (a)
- Vibration <math><2.5 \text{ m/sec}^2</math>
- Length 163 mm
- Weight 1.36 kg
- Air Inlet 1/4" BSP



+ 44 (1) 494 883300  
sales@ut-tools.com



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM



# **UT 5825-3/8CK**

3/8" Reversible Drill chuck and key

- **Chuck Type** chuck and key
- **Chuck Size** 3/8"
- **Motor Power** 0.40 HP
- **Free Speed** 1800 RPM
- **Air Cons** 4 CFM
- **Sound** 91 dB (a)
- **Vibration** <2.5 m/sec<sup>2</sup>
- **Length** 163 mm
- **Weight** 1.36 kg
- **Air Inlet** 1/4" BSP



+ 44 (1) 494 883300  
[sales@ut-tools.com](mailto:sales@ut-tools.com)



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM



# UT8741A

3/8" Drill Straight

- Chuck Type Chuck & Key
- Chuck Size 3/8"
- Free Speed 4500 RPM
- Air Cons 4 CFM
- Sound 94 dB (a)
- Vibration 2.5 m/sec<sup>2</sup>
- Length 220 mm
- Weight 1.13 kg
- Air Inlet 1/4" BSP



+ 44 (1) 494 883300  
sales@ut-tools.com



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM

# **UT 8806-3/8K**

3/8" Angle Drill - Keyless 1800 rpm

- **Chuck Type Keyless**
- **Chuck Size 3/8"**
- **Motor Power 0.50 HP**
- **Free Speed 1800 RPM**
- **Air Cons 3.7 CFM**
- **Sound 86 dB (a)**
- **Vibration 3.6 m/sec<sup>2</sup>**
- **Length 193 mm**
- **Weight 1.2 kg**
- **Air Inlet 1/4" BSP**



**+ 44 (1) 494 883300**  
**sales@ut-tools.com**



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM

# **UT 8806-3/8CK**

3/8" Angle Drill - Chuck & Key 1800 rpm

- **Chuck Type Chuck & Key**
- **Chuck Size 3/8"**
- **Motor Power 0.50 HP**
- **Free Speed 1800 RPM**
- **Air Cons 3.7 CFM**
- **Sound 86 dB (a)**
- **Vibration 3.6 m/sec<sup>2</sup>**
- **Length 193 mm**
- **Weight 1.2 kg**
- **Air Inlet 1/4" BSP**



**+ 44 (1) 494 883300**  
**sales@ut-tools.com**



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM





# **UT 8807B-3/8K**

3/8" Reversible Angle Head Drill Keyless

- **Chuck Type Keyless**
- **Chuck Size 3/8"**
- **Motor Power 0.5 HP**
- **Free Speed 1300 RPM**
- **Air Cons 4 CFM**
- **Sound 83.8 dB (a)**
- **Vibration <math><2.5 \text{ m/sec}^2</math>**
- **Length 202 mm**
- **Weight 1.2 kg**
- **Air Inlet 1/4" BSP**



**+ 44 (1) 494 883300**  
**sales@ut-tools.com**



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM



# **UT 8807B-3/8CK**

3/8" Reversible Angle Head Drill Chuck & Key

- **Chuck Type Chuck & Key**
- **Chuck Size 3/8"**
- **Motor Power 0.5 HP**
- **Free Speed 1300 RPM**
- **Air Cons 4 CFM**
- **Sound 83.8 dB (a)**
- **Vibration <math><2.5 \text{ m/sec}^2</math>**
- **Length 202 mm**
- **Weight 1.2 kg**
- **Air Inlet 1/4" BSP**



**+ 44 (1) 494 883300**  
**sales@ut-tools.com**



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HITCHAM COMBES, HPL4 3BY  
UNITED KINGDOM

# **UT 8821-3/8K**

3/8" Drill - Keyless 2600rpm

- **Chuck Type Keyless**
- **Chuck Size 3/8"**
- **Motor Power 0.50 HP**
- **Free Speed 2600 RPM**
- **Air Cons 3.7 CFM**
- **Sound 91 dB (a)**
- **Vibration 1.2 m/sec<sup>2</sup>**
- **Length 193 mm**
- **Weight 0.90 kg**
- **Air Inlet 1/4" BSP**



**+ 44 (1) 494 883300**  
**sales@ut-tools.com**



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM





# UT 8821-3/8CK

3/8" Drill - Chuck & Key 2600rpm

- Chuck Type Chuck and Key
- Chuck Size 3/8"
- Motor Power 0.50 HP
- Free Speed 2600 RPM
- Air Cons 3.7 CFM
- Sound 91 dB (a)
- Vibration 1.2 m/sec<sup>2</sup>
- Length 193 mm
- Weight 0.90 kg
- Air Inlet 1/4" BSP



+ 44 (1) 494 883300  
sales@ut-tools.com



**UNIVERSAL  
AIR TOOLS**

UNIVERSAL AIR TOOL CO., LTD  
UNIT 8, LANE END INDUSTRIAL PARK  
HIGH WYCOMBE, HP14 3BY  
UNITED KINGDOM