

HYDRAULIC OIL



Premium grade hydraulic oil

High viscosity index

Supplied in a choice of 1, 5 or 25 litre containers

- ▶ Effective and reliable lubricant
- ▶ Foaming resistance
- ▶ Provides optimum performance in all high pressure applications
- ▶ Specially formulated for use with all Hi-Force hydraulic tools

Model number	Contents (litres)
HFO15-25	25
HFO46-1	1
HFO46-5	5
HFO46-25	25

OIL TYPE RECOMMENDATION

Product	Oil Type		Product	Oil Type		Product	Oil Type	
	HFO15	HFO46		HFO15	HFO46		HFO15	HFO46
ACP	✓	•	HHA	•	✓	HVL	•	✓
AHP/AHP-CR/AHP2/AHP2-CR/ATDP	•	✓	HHP	•	✓	HWRC	•	✓
AHP-BTU	•	✓	HHR	•	✓	JAH	✓	•
AHP11	•	✓	HHS	•	✓	JAS	✓	•
BC	•	✓	HKP	✓	•	JCS/JCH	✓	✓
BPP	•	✓	HLS	•	✓	JS	✓	•
CH	•	✓	HMJ	•	✓	Manifolds	✓	✓
Controlled Manifolds	✓	✓	HMNS	✓	•	MHX	✓	•
Couplers & Fittings	✓	✓	Hoses	✓	✓	NS	•	✓
CT	✓	•	HP(All)	✓	•	PB	✓	•
Digital Gauge	✓	✓	HP-FP	✓	•	PKC	✓	•
DNS	•	✓	HPC	•	✓	PKS	✓	•
Gauge/Blocks	✓	✓	HPF	•	✓	PMV2	•	✓
HAP	-	✓	HPP	-	✓	PMV3/PMV3L	•	✓
HAS	•	✓	HPR/HBR	✓	•	PMV4/PMV4L	•	✓
HCC	•	✓	HPS	•	✓	RMV3/RMV3L	•	✓
HCH	•	✓	HPT	✓	✓	RMV4/RMV4L	•	✓
HDA	•	✓	HPX	✓	•	SBT	•	✓
HEP1	•	✓	HPX-BTU	✓	✓	SC	✓	•
HEP103	•	✓	HPV152	✓	✓	SCP	✓	•
HEP2/HEP3/HEP4/HEP5	-	✓	HRA	•	✓	SJS	✓	•
HFA	•	✓	HSG	•	✓	SLF/SLV	-	✓
HFG	•	✓	HSP	-	✓	STS	•	✓
HFL	•	✓	HSS	•	✓	STU	•	✓
HFS-H	•	✓	HSWC	✓	•	Toughlift	•	✓
HFV42/HFV66	✓	✓	HTN	•	✓	TPA	-	✓
HGG	•	✓	HTWP	-	✓	TPE	-	✓
			HTWR1	•	✓	XHR1	•	✓

Note: ✓ Recommended and factory fitted grade
 • Acceptable alternative
 - Not recommended